



DCUPS2U

- Unbreakable DC Power Supply (UPS), Subrack, 2U 84HP D=280mm
- Integrated Battery Pack
- 2 internal, independent Power Supplies for Continuous Operation and Battery Charging
- Zero voltage drop at powerswitch between mains supply and battery supply
- AC-Fail, DC-Fail Charger und Main Power Supply, O-Ring

□

DCUPS2U

Model	DCUPS2U		
Power	114W		
Master-slave operation	Slave-Units for modular capacity expansion available		
Master Vout	12V	24V	48V
Continuous Current	8A	4A	2A
Backup Capacity	16Ah	8Ah	4Ah
'19"-Subframe'	2U 84HP 280mm		
Mains Input	184... 265Vac (230Vac) 47-63Hz		
Mains Input Connector	Inlet connector male with Lock		
Monitoring	Relay, piezo-sound interval		
AC Power Fail	yes		
Battery Low Voltage	Signaling for relay		
Battery O.K.	LED & signal		
Battery Charger	Integrated		
Monitoring Battery Charger	Relay, Sub-D		
Power Supply	Active during mains operation for load		
Monitoring Power Supply	Relay, Sub-D		
Short Circuit Protection DC for Battery	Thermic fuse, manual resettable		
Cooling	Natural convection		
Efficiency	>90% continuous operation		
Operating Temperature	+10°C... +40°C, IEC60068-2-1		
Connection Output	Phoenix Power Combicon, screw-lock		
Battery Type	Built-in, type Panasonic LCR124R5P for cycle operation		
GND-Type DC	Plus connected GND		
PE Connection	Additional for front screw terminals		