



HSE01201

HSE01201 120W DIN-Rail

- DIN-Rail 1phase Fixed Output TS35mm
- Ideal vertically C/V chart for complex loads and battery charging

HSE01201

Model	HSE01201(R2)								
Power	120W								
Nominal AC Input	115/230Vac selector								
Input Range AC	90-115Vac/184-264Vac								
Input Range DC	250-375Vdc								
Hold-Up Time	30ms								
Inrush Current Protection	NTC < 16A								
Autostart	Soft start								
Output Voltage	12V	15V	24V	36V	48V	60V	72V	110V	
Adjust Range Vout	11,4-13,2V	14,2-16,5V	23,5-28,5V	34,2V-39,6V	45,6-42,8V	57,0-66,0V	68,0-86,0V	100,0-120,0V	
Ripple & Noise mVpp	50mV	50mV	65mV	65mV	100mV	120mV	120mV	200mV	
Nominal Output Current	8A	8A	5A	3,3A	2,5A	2A	1,7A	1,1A	
Efficiency	91%								
Basic load	Idling-proof								
Short Circuit Protection	Continuous								
Cooling	Natural convection								
Dimensions (WxHxD)	50x124x96mm								
Safety Standards	EN61010-1, EN61010-2-201, EN62368-1, EN60204-1, EN60950-1								
Input to Output Isolation	3000Vac								
EMI	EN55032 class B, EN61000-6-3, EN61000-3-2 class A								
EMS	EN61000-6-2								
MTBF	600.000h								
Power Good Relay	Yes								