



HSE07201

## HSE07201 720W DIN-Rail

- DIN-Rail Power Supply 1phase fix output TS35mm DIN EN 50022
- Temperature Control
- Clean C/V chart without foldback, ideal for dc drives

## HSE07201

Model	HSE07201(R2)				
Power	720W				
Nominal AC Input	115/230Vac selector				
Input Range AC	90-115Vac/184-264Vac				
Input Range DC	250-375Vdc				
Hold-Up Time	40ms				
Inrush Current Protection	NTC				
Autostart	Soft start				
Output Voltage	12V	24V	36V	48V	60V
Adjust Range Vout	11,4-14,4V	22,8-28,8V	34,2-43,2V	45,6-52,8V	57,0V-66,0V
Ripple & Noise mVpp	50mV	50mV	100mV	100mV	120mV
Nominal Output Current	40A	30A	20A	15A	12A
Efficiency	91%				
Basic load	Idling-proof				
Short Circuit Protection	Continuous				
Cooling	Natural convection				
Dimensions (WxHxD)	200x130x115mm				
Safety Standards	EN61010-1, EN61010-2-201, EN62368-1, EN60204-1, EN60950-1				
Input to Output Isolation	3000Vac (4200Vac for the 48Vdc model)				
EMI	EN55032 class B, EN61000-6-3				
EMS	EN61000-6-2				
MTBF	500.000h				
Power Good Relay	Yes				