



HSW00751

HSW00751 75W DIN-Rail

- DIN-Rail 1phase Fixed Output TS35mm

HSW00751

Model	HSW00751(R2)				
Power	75W				
Nominal AC Input	100-240Vac				
Input Range AC	90-264Vac				
Input Range DC	110-375Vdc				
Hold-Up Time	40ms				
Inrush Current Protection	NTC				
Autostart	Soft start				
Output Voltage	5V	9V	12V	15V	24V
Adjust Range Vout	4,9-5,5V	8,6-9,9V	11,4-13,2V	14,3-16,5V	24,0-28,0V
Ripple & Noise mVpp	15mV	25mV	20mV	20mV	50mV
Nominal Output Current	7,5A	7,5A	6,0A	5,0A	3,2A
Efficiency	90%				
Basic load	Idling-proof				
Short Circuit Protection	Continuous				
Cooling	Natural convection				
Dimensions (WxHxD)	50x102x93,1mm				
Safety Standards	EN61010-1, EN61010-2-201, EN62368-1, EN60204-1, EN60950-1				
Input to Output Isolation	3000Vac				
EMI	EN55032 Klasse B, EN61000-6-3, EN61000-3-2 Klasse A				
EMS	EN61000-6-2				
MTBF	500.000h				
Power Good Relay	Yes				
Sense operation	Yes for 5V-model $\pm 200\text{mV}$				